





Date of compilation: 3/6/2019      Revised: 5/25/2021      Version: 2 (Replaced 1)

**SECTION 1: IDENTIFICATION**

- 1.1 GHS Product identifier:** UF235 - Foamy Presoak 235  
**Other means of identification:**  
Non-applicable
- 1.2 Recommended use of the chemical and restrictions on use:**  
Relevant uses: Chemical cleaning products  
High foaming liquid mixtures for car washes.  
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party:**  
National Carwash Solutions  
1997 American Blvd  
54115 De Pere - United States  
Phone: 9203372175 - Fax: 9203379410  
<http://cleaningsystemsinc.com>
- 1.4 Emergency phone number:** 1-800-424-9300 or 1-703-527-3887

**SECTION 2: HAZARD(S) IDENTIFICATION**

- 2.1 Classification of the substance or mixture:**  
**NFPA:**  
Health Hazards: 3  
Flammability Hazards: 2  
Instability Hazards: 0  
Special Hazards: Non-applicable
- 29 CFR 1910.1200:**  
Classification of this product has been carried out in accordance with paragraph (d) of § 1910.1200.  
Carc. 2: Carcinogenicity, Category 2, H351  
Eye Dam. 1: Serious eye damage, Category 1, H318  
Flam. Liq. 4: Flammable liquids, Category 4, H227  
Skin Irrit. 2: Skin irritation, Category 2, H315
- 2.2 Label elements:**  
**NFPA:**  

- 29 CFR 1910.1200:**  
**Danger**  

- Hazard statements:**  
Carc. 2: H351 - Suspected of causing cancer.  
Eye Dam. 1: H318 - Causes serious eye damage.  
Flam. Liq. 4: H227 - Combustible liquid.  
Skin Irrit. 2: H315 - Causes skin irritation.
- Precautionary statements:**

- CONTINUED ON NEXT PAGE -



**UF235 - Foamy Presoak 235**

Date of compilation: 3/6/2019      Revised: 5/25/2021      Version: 2 (Replaced 1)

**SECTION 2: HAZARD(S) IDENTIFICATION (continued)**

P201: Obtain special instructions before use.  
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280: Wear protective gloves/protective clothing/eye protection/protective footwear.  
P302+P352: IF ON SKIN: Wash with plenty of soap and water.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313: IF exposed or concerned: Get medical advice/attention.  
P370+P378: In case of fire: Use ABC powder extinguisher to put it out.  
P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

**Substances that contribute to the classification**

Sodium Alkylsulfonates; Anionic Surfactants; Amides, coco, N,N-bis(hydroxyethyl); 2,2'-iminodiethanol

**Acute Toxicity Estimate (ATE mix):**

5.7 % (oral), 28.88 % (inhalation) of the mixture consists of ingredient(s) of unknown toxicity

**Additional labeling:**

Keep out of the reach of children

**2.3 Hazards not otherwise classified (HNOC):**

Non-applicable

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**3.1 Substances:**

Non-applicable

**3.2 Mixtures:**

**Chemical description:** Aqueous mixture composed of chemical products for cleaning products

**Components:**

Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

Identification	Chemical name/Classification	Concentration
CAS: Proprietary	<b>Sodium Alkylsulfonates</b> Eye Dam. 1: H318; Skin Irrit. 2: H315 - Danger	15 - <35 %
CAS: Proprietary	<b>Anionic Surfactants</b> Eye Dam. 1: H318; Skin Irrit. 2: H315 - Danger	5 - <10 %
CAS: 111-76-2	<b>2-butoxyethanol</b> Acute Tox. 4: H302+H332; Eye Irrit. 2A: H319; Flam. Liq. 4: H227; Skin Irrit. 2: H315 - Warning	5 - <10 %
CAS: 68603-42-9	<b>Amides, coco, N,N-bis(hydroxyethyl)</b> Carc. 2: H351; Eye Irrit. 2A: H319; Skin Irrit. 2: H315 - Warning	<5 %
CAS: 111-42-2	<b>2,2'-iminodiethanol</b> Acute Tox. 4: H302; Carc. 2: H351; Eye Dam. 1: H318; Skin Irrit. 2: H315; STOT RE 2: H373 - Danger	<5 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

**SECTION 4: FIRST-AID MEASURES**

**4.1 Description of necessary measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

This product is not classified as hazardous through inhalation, however, it is recommended in case of intoxication symptoms to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

- CONTINUED ON NEXT PAGE -



#### SECTION 4: FIRST-AID MEASURES (continued)

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

**4.2 Most important symptoms/effects, acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of immediate medical attention and special treatment needed, if necessary:**

Non-applicable

#### SECTION 5: FIRE-FIGHTING MEASURES

**5.1 Suitable (and unsuitable) extinguishing media:**

**Suitable extinguishing media:**

Combustible liquid. If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>).

**Unsuitable extinguishing media:**

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

**5.2 Specific hazards arising from the chemical:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Special protective equipment and precautions for fire-fighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

**Additional provisions:**

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

**6.1 Personal precautions, protective equipment and emergency procedures:**

**For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Evacuate the area and keep out those who do not have protection.

**For emergency responders:**

See section 8.

**6.2 Environmental precautions:**

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

**6.3 Methods and materials for containment and cleaning up:**

- CONTINUED ON NEXT PAGE -



Date of compilation: 3/6/2019      Revised: 5/25/2021      Version: 2 (Replaced 1)

**SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)**

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

**6.4 Reference to other sections:**

See sections 8 and 13.

**SECTION 7: HANDLING AND STORAGE**

**7.1 Precautions for safe handling:**

A.- General precautions for safe use

Comply with the current standards 29 CFR 1910 Occupational Safety and Health Standards. Maintain order, cleanliness and destroy using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, manipulation and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

**7.2 Conditions for safe storage, including any incompatibilities:**

A.- Technical measures for storage

Minimum Temp.: 24.8 °F

Maximum Temp.: 120 °F

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace:

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000):

Identification	Occupational exposure limits		
	8-hour TWA PEL	50 ppm	240 mg/m <sup>3</sup>
2-butoxyethanol CAS: 111-76-2	Ceiling Values - TWA PEL		

US. ACGIH Threshold Limit Values (2022):

Identification	Occupational exposure limits		
	TLV-TWA	20 ppm	
2-butoxyethanol CAS: 111-76-2	TLV-STEL		
2,2'-iminodiethanol CAS: 111-42-2	TLV-TWA		2 mg/m <sup>3</sup>
	TLV-STEL		
2,2',2''-nitrioltriethanol CAS: 102-71-6	TLV-TWA		5 mg/m <sup>3</sup>
	TLV-STEL		

- CONTINUED ON NEXT PAGE -



**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

**CALIFORNIA- TABLE AC-1 PERMISSIBLE EXPOSURE LIMITS FOR CHEMICAL CONTAMINANTS:**

Identification	Occupational exposure limits		
	PEL	STEL	Other
2-butoxyethanol CAS: 111-76-2	20 ppm		97 mg/m <sup>3</sup>
2,2'-iminodiethanol CAS: 111-42-2	0.46 ppm		2 mg/m <sup>3</sup>
2,2',2''-nitritotriethanol CAS: 102-71-6			5 mg/m <sup>3</sup>

**Biological limit values:**

**Biological Exposure Indices (BEIs®) - ACGIH**

Identification	BEIs®	Determinant	Sampling Time
2-butoxyethanol CAS: 111-76-2	200 mg/g (NULL)	Butoxyacetic acid (BAA) in urine	End of shift

**8.2 Appropriate engineering controls:**

**A.- Individual protection measures, such as personal protective equipment**

As a preventative measure it is recommended to use basic Personal Protection Equipment. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

**B.- Respiratory protection**

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

**C.- Specific protection for the hands**

Pictogram	PPE	Remarks
Mandatory hand protection	Protective gloves against minor risks	Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional /industrial users, we recommend using chemical protection gloves. Use gloves in accordance with manufacturer's use limitations and OSHA standard 1910.138 (29CFR)

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

**D.- Eye and face protection**

Pictogram	PPE	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. Use this PPE in accordance with manufacturer's use limitations and OSHA standard 1910.133 (29CFR)

**E.- Bodily protection**

Pictogram	PPE	Remarks
	Work clothing	Replace before any evidence of deterioration.
	Anti-slip work shoes	Replace before any evidence of deterioration.



**F.- Additional emergency measures**

- CONTINUED ON NEXT PAGE -



Date of compilation: 3/6/2019      Revised: 5/25/2021      Version: 2 (Replaced 1)

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**40 CFR Part 59 (VOC):**

V.O.C.(weight-percent):                      5 % weight  
V.O.C. at 68 °F:                                144.85 kg/m<sup>3</sup> (144.85 g/L)

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

Physical state at 68 °F:                      Liquid  
Appearance:                                    Semitransparent  
Color:    Blue  
Odor:    Not available  
Odour threshold:                                Non-applicable \*

**Volatility:**

Boiling point at atmospheric pressure:    218 °F  
Vapour pressure at 68 °F:                    2323 Pa  
Vapour pressure at 122 °F:                   12240.42 Pa (12.24 kPa)  
Evaporation rate at 68 °F:                    Non-applicable \*

**Product description:**

Density at 68 °F:                                1038.1 kg/m<sup>3</sup>  
Relative density at 68 °F:                    1.038  
Dynamic viscosity at 68 °F:                   Non-applicable \*  
Kinematic viscosity at 68 °F:                Non-applicable \*  
Kinematic viscosity at 104 °F:              Non-applicable \*  
Concentration:                                    Non-applicable \*  
pH:    10.5 - 11.5 (at 100 %)  
Vapour density at 68 °F:                      Non-applicable \*  
Partition coefficient n-octanol/water 68 °F: Non-applicable \*  
Solubility in water at 68 °F:                   Non-applicable \*  
Solubility properties:                          Non-applicable \*  
Decomposition temperature:                Non-applicable \*  
Melting point/freezing point:                Non-applicable \*

**Flammability:**

Flash Point:                                        157 °F  
Flammability (solid, gas):                    Non-applicable \*  
Autoignition temperature:                    460 °F

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -





**UF235 - Foamy Presoak 235**

Date of compilation: 3/6/2019

Revised: 5/25/2021

Version: 2 (Replaced 1)

**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

**A- Ingestion (acute effect):**

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

**B- Inhalation (acute effect):**

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**C- Contact with the skin and the eyes (acute effect):**

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces serious eye damage after contact.

**D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):**

- Carcinogenicity: Exposure to this product can cause cancer. For more specific information on the possible health effects see section 2.  
IARC: 2-butoxyethanol (3); Amides, coco, N,N-bis(hydroxyethyl) (2B); 2,2'-iminodiethanol (2B); 2,2',2''-nitrioltriethanol (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**E- Sensitizing effects:**

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**F- Specific target organ toxicity (STOT) - single exposure:**

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**G- Specific target organ toxicity (STOT)-repeated exposure:**

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, however, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**H- Aspiration hazard:**

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**Other information:**


Non-applicable

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Sodium Alkylsulfonates CAS: Proprietary	2290 mg/kg	6300 mg/kg	Rat
		Non-applicable	Rabbit
2-butoxyethanol CAS: 111-76-2	1200 mg/kg	3000 mg/kg	Rat
		11 mg/L (ATEi)	Rabbit

- CONTINUED ON NEXT PAGE -





Date of compilation: 3/6/2019

Revised: 5/25/2021

Version: 2 (Replaced 1)

**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

Identification	Acute toxicity		Genus
	Route	Dose	
Amides, coco, N,N-bis(hydroxyethyl) CAS: 68603-42-9	LD50 oral	12200 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
2,2'-iminodiethanol CAS: 111-42-2	LD50 oral	710 mg/kg	Rat
	LD50 dermal	12200 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	

**Acute Toxicity Estimate (ATE mix):**

ATE mix		Ingredient(s) of unknown toxicity
Oral	24000 mg/kg (Calculation method)	5.7 %
Dermal	>5000 mg/kg (Calculation method)	Non-applicable
Inhalation	156.46 mg/L (4 h) (Calculation method)	28.88 %

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

**12.1 Ecotoxicity (aquatic and terrestrial, where available):**

**Acute toxicity:**

Identification	Concentration		Species	Genus
	Route	Dose		
Sodium Alkylsulfonates CAS: Proprietary	LC50	4.2 mg/L (96 h)	Brachydanio rerio	Fish
	EC50	4.53 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	5.2 mg/L (72 h)	Skeletonema costatum	Algae
2-butoxyethanol CAS: 111-76-2	LC50	1490 mg/L (96 h)	Lepomis macrochirus	Fish
	EC50	1815 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	911 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
2,2'-iminodiethanol CAS: 111-42-2	LC50	800 mg/L (24 h)	Carassius auratus	Fish
	EC50	180 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	75 mg/L (72 h)	Scenedesmus subspicatus	Algae

**Chronic toxicity:**

Identification	Concentration		Species	Genus
	Route	Dose		
Sodium Alkylsulfonates CAS: Proprietary	NOEC	Non-applicable		
	NOEC	6.3 mg/L	Daphnia magna	Crustacean
2-butoxyethanol CAS: 111-76-2	NOEC	100 mg/L	Danio rerio	Fish
	NOEC	100 mg/L	Daphnia magna	Crustacean

- CONTINUED ON NEXT PAGE -



SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Concentration		Species	Genus
2,2'-iminodiethanol CAS: 111-42-2	NOEC	1 mg/L	N/A	Fish
	NOEC	0.78 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
Sodium Alkylsulfonates CAS: Proprietary	BOD5	Non-applicable	Concentration	20 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	96 %
2-butoxyethanol CAS: 111-76-2	BOD5	0.71 g O2/g	Concentration	100 mg/L
	COD	2.2 g O2/g	Period	14 days
	BOD5/COD	0.32	% Biodegradable	96 %
2,2'-iminodiethanol CAS: 111-42-2	BOD5	0.03 g O2/g	Concentration	100 mg/L
	COD	1.52 g O2/g	Period	21 days
	BOD5/COD	0.02	% Biodegradable	54 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
Sodium Alkylsulfonates CAS: Proprietary	BCF	71
	Pow Log	-1.3
	Potential	Moderate
2-butoxyethanol CAS: 111-76-2	BCF	3
	Pow Log	0.83
	Potential	Low
2,2'-iminodiethanol CAS: 111-42-2	BCF	1
	Pow Log	-1.43
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Sodium Alkylsulfonates CAS: Proprietary	Koc	1.6	Henry	6.7E-2 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
2-butoxyethanol CAS: 111-76-2	Koc	8	Henry	1.621E-1 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	No
	Surface tension	2.729E-2 N/m (77 °F)	Moist soil	Yes

- CONTINUED ON NEXT PAGE -



Date of compilation: 3/6/2019      Revised: 5/25/2021      Version: 2 (Replaced 1)

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Identification	Absorption/desorption		Volatility	
	2,2'-iminodiethanol CAS: 111-42-2	Koc	Non-applicable	Henry
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	3.4E-2 N/m (299.21 °F)	Moist soil	Non-applicable

**12.5 Results of PBT and vPvB assessment:**

Non-applicable

**12.6 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Disposal methods:**

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations. In case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See epigraph 6.2.

**Regulations related to waste management:**

Legislation related to waste management:

40 CFR Part 261- IDENTIFICATION AND LISTING OF HAZARDOUS WASTE

**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:**

With regard to 49 CFR on the Transport of Dangerous Goods:



- 14.1 UN number:** NA1993
- 14.2 UN proper shipping name:** Combustible liquid, n.o.s.
- 14.3 Transport hazard class(es):** 3
- Labels: 3

- 14.4 Packing group, if applicable:** III
- 14.5 Marine pollutant:** No

**14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**

Physico-Chemical properties: see section 9  
Limited quantities: 5 L

49 CFR 173.150: It can be shipped as a non-hazardous material if the container is under 120 gallons

- 14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Non-applicable

**Transport of dangerous goods by sea:**

With regard to IMDG 40-20:

- CONTINUED ON NEXT PAGE -



**SECTION 14: TRANSPORT INFORMATION (continued)**

- 14.1 UN number: Non-applicable
- 14.2 UN proper shipping name: Non-applicable
- 14.3 Transport hazard class(es): Non-applicable  
Labels: Non-applicable
- 14.4 Packing group, if applicable: Non-applicable
- 14.5 Marine pollutant: No
- 14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises  
Special regulations: Non-applicable  
EmS Codes:  
Physico-Chemical properties: see section 9  
Limited quantities: Non-applicable  
Segregation group: Non-applicable
- 14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Non-applicable

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2022:

- 14.1 UN number: Non-applicable
- 14.2 UN proper shipping name: Non-applicable
- 14.3 Transport hazard class(es): Non-applicable  
Labels: Non-applicable
- 14.4 Packing group, if applicable: Non-applicable
- 14.5 Marine pollutant: No
- 14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises  
Physico-Chemical properties: see section 9
- 14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Non-applicable

**SECTION 15: REGULATORY INFORMATION**

- 15.1 Safety, health and environmental regulations specific for the product in question:

- CONTINUED ON NEXT PAGE -



## UF235 - Foamy Presoak 235

Date of compilation: 3/6/2019

Revised: 5/25/2021

Version: 2 (Replaced 1)

### SECTION 15: REGULATORY INFORMATION (continued)

Toxic chemical release reporting under EPCRA section 313 (40 CFR Part 372): 2-butoxyethanol ; 2,2'-iminodiethanol  
California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Cancer: Amides, coco, N,N-bis (hydroxyethyl) ; 2,2'-iminodiethanol

The Toxic Substances Control Act (TSCA) : Sodium Alkylsulfonates ; Anionic Surfactants ; 2-butoxyethanol ; Amides, coco, N,N-bis(hydroxyethyl) ; 2,2'-iminodiethanol

Massachusetts RTK - Substance List: 2-butoxyethanol ; 2,2'-iminodiethanol

New Jersey Worker and Community Right-to-Know Act: 2-butoxyethanol ; 2,2'-iminodiethanol

New York RTK - Substance list: 2-butoxyethanol ; 2,2'-iminodiethanol

Pennsylvania Worker and Community Right-to-Know Law: 2-butoxyethanol ; 2,2'-iminodiethanol

CANADA-Domestic Substances List (DSL): Sodium Alkylsulfonates ; Anionic Surfactants ; 2-butoxyethanol ; Amides, coco, N,N-bis(hydroxyethyl) ; 2,2'-iminodiethanol

CANADA-Non-Domestic Substances List (NDSL): Non-applicable

NTP (National Toxicology Program): Non-applicable

Minnesota - Hazardous substances ERTK: 2-butoxyethanol ; 2,2'-iminodiethanol

Rhode Island - Hazardous substances RTK: 2-butoxyethanol ; 2,2'-iminodiethanol

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096): Non-applicable

Hazardous Air Pollutants (Clean Air Act): 2-butoxyethanol ; 2,2'-iminodiethanol

CALIFORNIA LABOR CODE - The Hazardous Substances List: 2-butoxyethanol ; 2,2'-iminodiethanol

California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Birth defects or other reproductive harm: Non-applicable

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantities: 2-butoxyethanol (1 pounds) ; 2,2'-iminodiethanol (100 pounds)

#### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

#### Other legislation:

Take into consideration other applicable federal, state, and local laws and local regulations.

### SECTION 16: OTHER INFORMATION

#### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets

#### Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation.

H318: Causes serious eye damage.

H351: Suspected of causing cancer.

H227: Combustible liquid.

#### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

#### 29 CFR 1910.1200:

Acute Tox. 4: H302 - Harmful if swallowed.

Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled.

Carc. 2: H351 - Suspected of causing cancer.

Eye Dam. 1: H318 - Causes serious eye damage.

Eye Irrit. 2A: H319 - Causes serious eye irritation.

Flam. Liq. 4: H227 - Combustible liquid.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

#### Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

#### Principal bibliographical sources:

- CONTINUED ON NEXT PAGE -



UF235 - Foamy Presoak 235

Date of compilation: 3/6/2019      Revised: 5/25/2021      Version: 2 (Replaced 1)

SECTION 16: OTHER INFORMATION (continued)

Occupational Safety & Health Administration (OSHA).

**Abbreviations and acronyms:**

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

CL50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient

Koc: Partition coefficient of organic carbon

IARC: International Agency for Research on Cancer

Date of compilation: 3/6/2019

Revised: 5/25/2021

Manufacturer Disclaimer: The information contained in this safety data sheet ("SDS") is based on sources, technical knowledge and current legislation. Furthermore, is based on data believed to be accurate; thus, the company does not assume any liability for its accuracy. The information provided herein cannot be considered a guarantee of the properties of this product and the same is simply a description of the security requirements. The use, occupational methodology and/or conditions for users of this product are not within our awareness or control. It is ultimately the responsibility of the user(s) to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information of this SDS only refers to this product, which should not be used for purposes other than those specified. Finally, the manner in which this product is used and whether there is any infringement of patents is the sole responsibility of the user(s).

END OF SAFETY DATA SHEET