

SECTION 1: IDENTIFICATION

1.1 GHS Product identifier: UF240 - High Pressure Detergent Lemon Lime 240

1.2 Recommended use of the chemical and restrictions on use:

Relevant uses: Chemical cleaning products

High foaming liquid mixtures for car washes.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party:

Cleaning Systems, Inc. 1997 American Blvd 54115 De Pere - United States Phone.: 9203372175 - Fax: 9203379410 chemcompliance@cleaningsystemsinc.com http://cleaningsystemsinc.com

1.4 Emergency phone number: 1-800-424-9300 or 1-703-527-3887

SECTION 2: HAZARD(S) IDENTIFICATION

2.1 Classification of the substance or mixture:

29 CFR 1910.1200:

Classification of this product has been carried out in accordance with paragraph (d) of § 1910.1200.

Carc. 2: Carcinogenicity, Category 2, H351 Eye Dam. 1: Serious eye damage, Category 1, H318 Skin Irrit. 2: Skin irritation, Category 2, H315

2.2 Label elements:

29 CFR 1910.1200:

Danger



Hazard statements:

Carc. 2: H351 - Suspected of causing cancer Eye Dam. 1: H318 - Causes serious eye damage Skin Irrit. 2: H315 - Causes skin irritation

Precautionary statements:

P201: Obtain special instructions before use

P264: Wash thoroughly after use

P280: Wear protective gloves/protective clothing/eye protection/face protection

P302+P352: IF ON SKIN: Wash with plenty of soap and water

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P308+P313: IF exposed or concerned: Get medical advice/attention

P310: Immediately call a poison center/doctor

P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively

Substances that contribute to the classification

Sodium Alkylsulfonates; Anionic Surfactants; Amides, coco, N,N-bis(hydroxyethyl); Diethanolamine

Acute Toxicity Estimate (ATE mix):

17.13 % (oral), 20.19 % (dermal), 40.31 % (inhalation) of the mixture consists of ingredient(s) of unknown toxicity

2.3 Other hazards which do not result in classification:

Non-applicable



3.1 Substances:

Non-applicable

3.2 Mixtures:

Chemical description: Aqueous mixture composed of chemical products for cleaning products

Components:

Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

entification	Chemical name/Classification	Concentration
roprietary	Sodium Alkylsulfonates Eve Dam 1: H318: Skin Irrit 2: H315 - Danger	15 - <35 %
roprietary	Anionic Surfactants	15 - <35 %
11-76-2		5 - <10 %
3603-42-9		<5 %
11-42-2	Diethanolamine Acute Tox. 4: H302; Carc. 2: H351; Eye Dam. 1: H318; Skin Irrit. 2: H315; STOT RE 2: H373 - Danger	<5 %
n 1	oprietary oprietary 1-76-2 603-42-9 1-42-2	Sodium Alkylsulfonates Eye Dam. 1: H318; Skin Irrit. 2: H315 - Danger Anionic Surfactants Eye Dam. 1: H318; Skin Irrit. 2: H315 - Danger Anionic Surfactants Eye Dam. 1: H318; Skin Irrit. 2: H315 - Danger 2-butoxyethanol Acute Tox. 4: H302+H312+H332; Eye Irrit. 2: H319; Flam. Liq. 4: H227; Skin Irrit. 2: H315 - Warning 603-42-9 Amides, coco, N,N-bis(hydroxyethyl) Carc. 2: H351; Eye Irrit. 2: H319; Skin Irrit. 2: H315 - Warning Diethanolamine

SECTION 4: FIRST-AID MEASURES

4.1 Description of necessary measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation,however, it is recommended in case of intoxication symptoms to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms/effects, acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of immediate medical attention and special treatment needed, if necessary:

Non-applicable

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Suitable (and unsuitable) extinguishing media:



SECTION 5: FIRE-FIGHTING MEASURES (continued)

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. IT IS NOT RECOMMENDED to use tap water as an extinguishing agent.

5.2 Specific hazards arising from the chemical:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Special protective equipment and precautions for fire-fighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and materials for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current standards 29 CFR 1910 Occupational Safety and Health Standards. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, manipulation and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

Minimum Temp.:	-4 °F
Maximum Temp.:	120 ºF



SECTION 7: HANDLING AND STORAGE (continued)

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace

Identification		Environmental limits			
2-butoxyethanol	8-hour TWA PEL	50 ppm	240 mg/m ³		
CAS: 111-76-2	Ceiling Values - TW PEL	Ά			

8.2 Appropriate engineering controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protection Equipment. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation, the information on clothing performance must be combined with professional judgment, and a clear understanding of the clothing application, to provide the best protection to the worker. All chemical protective clothing use must be based on a hazard assessment to determine the risks for exposure to chemicals and other hazards. Conduct hazard assessments in accordance with 29 CFR 1910.132.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Pictogram	PPE	Remarks
Mandatory hand	Protective gloves against minor risks	Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional <i>l</i> industrial users, we recommend using chemical protection gloves. Use gloves in accordance with manufacturer's use limitations and OSHA standard 1910.138 (29CFR)

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application

D.- Ocular and facial protection

	Pictogram	PPE	Remarks
	Mandatory face protection	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. Use this PPE in accordance with manufacturer's use limitations and OSHA standard 1910.133 (29CFR)
E	Bodily protection		

	Pictogram	PPE	Remarks			
		Work clothing	Replace before any evidence of deterioration.			
		Anti-slip work shoes	Replace before any evidence of deterioration.			
F	F Additional emergency measures					



Initial States 1DevelopmentEnvironmental exposure controls:In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental gas of both the product and its container. For additional information see subsection 7.1.0Information on basic physical and chemical properties:For complete information see the product datasheet.Appearance:ViscousOdio:Not availableOdio:ViscousColor:ViscousColor:ViscousOdio:ViscousOdio:ViscousOdio:ViscousOdio:ViscousOdio:Non-applicable *ViscousOdio:ViscousOdio:ViscousOdio:ViscousOdio:ViscousOdio:ViscousOdio:ViscousViscousOdio:ViscousOdio:ViscousOdio:ViscousOdi		Emergency measure	Standards	Emergency measure	Standards	
In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D TION 9: PHYSICAL AND CHEMICAL PROPERTIES Information on basic physical and chemical properties: For complete information see the product datasheet. Appearance: Physical state at 68 °F: Liquid Appearance: Viscous Color: Not available Odour threshold: Volatility: Boiling point at atmospheric pressure: 219 °F Vapour pressure at 68 °F: Vapour pressure at 68 °F: Vapour pressure at 68 °F: Physical state of 68 °F: Density at 68 °F: Density at 68 °F: Non-applicable *		IS				
spillage of both the product and its container. For additional information see subsection 7.1.D TION 91 PHYSICAL AND CHEMICAL PROPERTIES Information on basis physical and chemical properties: For complete information see the product datasheet. Appearance: Physical state at 68 °F: Physical state at 68 °F: Odor: Color: Col		Environmental exposure controls:				
CTION 9: PHYSICAL AND CHEMICAL PROPERTIES Information on basic physical and chemical properties: For complete information see the product datasheet. Appearance: Physical state at 68 °F: Liquid Appearance: Viscous Color: Turquoise Odor: Not available Odour threshold: Non-applicable * Volatility: Useous Boiling point at atmospheric pressure: 219 °F Vapour pressure at 68 °F: 2316 Pa Vapour pressure at 68 °F: 91.55 (12.21 kPa) Evaporation rate at 68 °F: Non-applicable * Product description: Density at 68 °F: Dynamic viscosity at 68 °F: Non-applicable * Kinematic viscosity at 68 °F: Non-applicable * Kinematic viscosity at 104 °F: >20.5 cSt Concentration: Non-applicable * pH: 10.5 - 11.5 at 100 % Vapour density at 68 °F: Non-applicable * Solubility moder at 68 °F: Non-applicable * Solubility properties: Non-applicable * Solubility mater at 68 °F: Non-applicable *		•	n for the protection	of the environment it is recomme	nded to avoid environmental	
Information on basic physical and chemical properties: For complete information see the product datasheet. Appearance: Physical state at 68 °F: Liquid Appearance: Viscous Color: Turquoise Odor: Not available Odor: Not available Odor: Not available Odor: Not available Odor threshold: Non-applicable * Valout threshold: Non-applicable * Vapour pressure at 68 °F: 2316 Pa Vapour pressure at 68 °F: Non-applicable * Product description: Evaporation rate at 68 °F: Density at 68 °F: 1040.2 kg/m³ Relative density at 68 °F: 1.04 Dynamic viscosity at 104 °F: >20.5 Cst Concentration: Non-applicable * Phi: 10.5 - 11.5 at 100 % Vapour density at 68 °F: Non-applicable * Portition coefficient n-octanol/water 68 °F: Non-applicable * Portition coefficient n-octanol/water 68 °F: Non-applicable * Polubility in vater at 68 °F: Non-applicable * Solubility properties: Non-applicab		spillage of both the product and its contained	r. For additional info	rmation see subsection 7.1.D		
Information on basic physical and chemical properties: For complete information see the product datasheet. Appearance: Physical state at 68 °F: Liquid Appearance: Viscous Color: Turquoise Odor: Not available Odor: Not available Odor: Not available Odor: Not available Odor threshold: Non-applicable * Valout threshold: Non-applicable * Vapour pressure at 68 °F: 2316 Pa Vapour pressure at 68 °F: Non-applicable * Product description: Evaporation rate at 68 °F: Density at 68 °F: 1040.2 kg/m³ Relative density at 68 °F: 1.04 Dynamic viscosity at 104 °F: >20.5 Cst Concentration: Non-applicable * Phi: 10.5 - 11.5 at 100 % Vapour density at 68 °F: Non-applicable * Portition coefficient n-octanol/water 68 °F: Non-applicable * Portition coefficient n-octanol/water 68 °F: Non-applicable * Polubility in vater at 68 °F: Non-applicable * Solubility properties: Non-applicab						
For complete information see the product datasheet.Appearance:LiquidPhysical state at 68 °F:ViscousColor:TurquoiseOdor:Not availableOdor:Not availableOdor:Non-applicable *Polling point at atmospheric pressure:29 °FVapour pressure at 68 °F:2316 PaVapour pressure at 122 °F:91.55 (12.21 kPa)Evaporation rate at 68 °F:Non-applicable *Polettive description:1040.2 kg/m³Product description:Non-applicable *Poince viscosity at 68 °F:1040.2 kg/m³Relative density at 68 °F:Non-applicable *Non-applicable *Non-applicable *Kinematic viscosity at 68 °F:Non-applicable *Pour density at 68 °F:Non-applicable *Kinematic viscosity at 68 °F:Non-applicable *Solubility in water at 68 °F:Non-applicable *Pour density at 68 °F:No	С	TION 9: PHYSICAL AND CHEMICAL	PROPERTIES			
Appearance:Physical state at 68 °F:LiquidAppearance:ViscousColor:TurquoiseOdor:Not-availableOdor:Non-applicable *Odur threshold:Non-applicable *Valility:219 °FPoluing point at atmospheric pressure:219 °FVapour pressure at 62 °F:2316 PaVapour pressure at 62 °F:55 (12.21 kPa)Vapour pressure at 62 °F:Non-applicable *Poduct description:Non-applicable *Ponduct description:1.04Density at 68 °F:Non-applicable *Relative density at 68 °F:Non-applicable *Kinematic viscosity at 68 °F:Non-applicable *Your description:>20.5 cStConcentration:Non-applicable *Phi:10.5 - 11.5 at 100 %Vapour density at 68 °F:Non-applicable *Solubility in vaper at 68 °F:Non-applicable *Solubility properties:Non-applicable *Potior consity at 68 °F:Non-applicable *Potior consition temperature:Non-applicable *Solubility properties:Non-applicable *Potior temperature:Non-applicable *Potioris:Non-applicable *Potioris:Non-applicable *Potioris:Non-applicable *Potioris:Non-applicable *Potioris:Non-applicable *Potioris:Non-applicable *Potioris:Non-applicable *Potioris:Non-applicable *Potioris:Non-applicable *		Information on basic physical and chemical	properties:			
Physical state at 68 °F:LiquidAppearance:ViscousColor:TurquoiseOdor:Not availableOdor:Not availableOdor:Non-applicable *Odor:Son-applicable *Bolling point at atmospheric pressure:219 °FVapour pressure at 68 °F:2316 PaVapour pressure at 68 °F:00-applicable *Paporation rate at 68 °F:0140.2 kg/m³Product description:040.2 kg/m³Product description:1.04Porticut description:1.04Porticut scosity at 68 °F:Non-applicable *Porticut scosity at 68 °F:1.04Porticut scosity at 68 °F:Non-applicable *Kinematic viscosity at 68 °F:Non-applicable *Porticut scosity at 68 °F:Non-applicable *Porticut scosity at 68 °F:Non-applicable *Porticut scosity at 68 °F:Non-applicable *Pour density at 68 °F: </td <td></td> <td>For complete information see the product d</td> <td>atasheet.</td> <td></td> <td></td>		For complete information see the product d	atasheet.			
Appearance:ViscousColor:TurquoiseOdor:Not availableOdor:Not availableOdour threshold:Non-applicable *Value219 °FSolling point at atmospheric pressure:219 °FVapour pressure at 68 °F:2316 PaVapour pressure at 122 °F:91.55 (12.21 kPa)Evaporation rate at 68 °F:Non-applicable *Product description:1.04Density at 68 °F:1.04Dynamic viscosity at 68 °F:Non-applicable *Relative density at 68 °F:Non-applicable *Kinematic viscosity at 68 °F:Non-applicable *Portue2.05 CStConcentration:Non-applicable *ph:1.05 - 11.5 at 100 %Vapour density at 68 °F:Non-applicable *pollity in water at 68 °F:Non-applicable *ph:1.05 - 11.5 at 100 %Vapour density at 68 °F:Non-applicable *pollity in water at 68 °F:Non-applicable *pollity in water at 68 °F:Non-applicable *Solubility in water at 68 °F:Non-applicable *Partition coefficient n-octanol/water 68 °F:Non-applicable *Solubility properties:Non-applicable *Decomposition temperature:Non-applicable *Decomposition temperature:Non-applicable *Partition poerties:Non-applicable *Point:Non-applicable *Point:Non-applicable *Point:Non-applicable *Point:Non-applicable *Point:Non		Appearance:				
NormOdor:TurquoiseOdor:Not availableOdor:Not availableOdour threshold:Non-applicable*Valutility:Boling point at atmospheric pressure:219 °FVapour pressure at 68 °F:2316 PaVapour pressure at 122 °F:91.55 (12.21 kPa)Evaporation rate at 68 °F:Non-applicable*Product description:Density at 68 °F:1.04Dynamic viscosity at 68 °F:Non-applicable*Nomapplicable*Non-applicable*Kinematic viscosity at 68 °F:Non-applicable*Kinematic viscosity at 68 °F:Non-applicable*Yapour density at 68 °F:Non-applicable*Yapour density at 68 °F:Non-applicable*PH:1.05 - 11.5 at 100 %Vapour density at 68 °F:Non-applicable*Solubility in water at 68 °F:Non-applicable*Policable *Non-applicable*Policable *Non-applicable*Solubility in water at 68 °F:Non-applicable*Solubility in water at 68 °F:Non-applicable*Decomposition temperature:Non-applicable*Decomposition temperature:Non-applicable*Metting point/freezing point:Non-applicable*Explosive properties:Non-applicable*Policable *Non-applicable*Policable *Non-applicable*Policable *Non-applicable*Policable *Non-applicable*Policable *Non-applicable*Policable *Non-applicable*<		Physical state at 68 °F:	Liquid			
Odor:Not availableOdour threshold:Non-applicable*Volatility:Volatility:Boiling point at atmospheric pressure:219 °FVapour pressure at 68 °F:2316 PaVapour pressure at 122 °F:91.55 (12.21 kPa)Evaporation rate at 68 °F:Non-applicable*Product description:1040.2 kg/m³Product description:1.04Density at 68 °F:Non-applicable*Non-applicable*Non-applicable*Kinematic viscosity at 68 °F:Non-applicable*Kinematic viscosity at 68 °F:Non-applicable*Vapour density at 68 °F:Non-applicable*PH:10.5 - 11.5 at 100 %Vapour density at 68 °F:Non-applicable*Puttion coefficient n-octanol/water 68 °F:Non-applicable*Solubility in water at 68 °F:Non-applicable*Puttion coefficient n-octanol/water 68 °F:Non-applicable*Solubility in water at 68 °F:Non-applicable*Decomposition temperature:Non-applicable*Metting point!Non-applicable*Solubility properties:Non-applicable*Particion cefficient n-octanol/water 68 °F:Non-applicable*Solubility in water at 68 °F:Non-applicable*Decomposition temperature:Non-applicable*Particion cefficient n-octanol/waterNon-applicable*		Appearance:	Viscou	S		
Odour threshold:Non-applicable*Volatility:Image: Constraint of the second of		Color:	Turquo	ise		
Volatility:Boiling point at atmospheric pressure:219 °FVapour pressure at 68 °F:2316 PaVapour pressure at 122 °F:91.55 (12.21 kPa)Evaporation rate at 68 °F:Non-applicable *Product description:1040.2 kg/m³Pelative density at 68 °F:1.04Dynamic viscosity at 68 °F:Non-applicable *Kinematic viscosity at 68 °F:Non-applicable *Kinematic viscosity at 68 °F:Non-applicable *Concentration:Non-applicable *PH:0.5 c StConcentration:Non-applicable *PH:Non-applicable *Vapour density at 68 °F:Non-applicable *Solubility in water at 68 °F:Non-applicable *Solubility in water at 68 °F:Non-applicable *Solubility in water at 68 °F:Non-applicable *Solubility properties:Non-applicable *Solubility properties:Non-applicable *Solubility properties:Non-applicable *Personposition temperature:Non-applicable *Personposition temperature:Non-applicable *Solubility properties:Non-applicable *Personposition temperature:Non-applicable *Personposition temperature: <td></td> <td>Odor:</td> <td>Not ava</td> <td>ailable</td> <td></td>		Odor:	Not ava	ailable		
Boiling point at atmospheric pressure:219 °FVapour pressure at 68 °F:2316 PaVapour pressure at 122 °F:91.55 (12.21 kPa)Evaporation rate at 68 °F:Non-applicable *Product description:Density at 68 °F:1040.2 kg/m³Relative density at 68 °F:1.04Dynamic viscosity at 68 °F:Non-applicable *Kinematic viscosity at 68 °F:Non-applicable *Kinematic viscosity at 68 °F:Non-applicable *Concentration:>20.5 cStConcentration:Non-applicable *PH:10.5 - 11.5 at 100 %Vapour density at 68 °F:Non-applicable *Solubility in water at 68 °F:Non-applicable *Partition coefficient n-octanol/water 68 °F:Non-applicable *Solubility in water at 68 °F:Non-applicable *Solubility in goint:Non-applicable *Solubility in goint:Non-applicable *Partition coefficient n-octanol/water 68 °F:Non-applicable *Solubility in goint:Non-applicable *Solubility in goint:Non-applicable *Partition coefficient n-octanol/water 68 °F:Non-applicable *Solubility in goint:Non-applicable *Solubility		Odour threshold:	Non-ap	plicable *		
Vapour pressure at 68 °F:2316 PaVapour pressure at 122 °F:91.55 (12.21 kPa)Evaporation rate at 68 °F:Non-applicable *Product description:Density at 68 °F:1040.2 kg/m³Relative density at 68 °F:1.04Dynamic viscosity at 68 °F:Non-applicable *Kinematic viscosity at 68 °F:Non-applicable *Kinematic viscosity at 68 °F:Non-applicable *Kinematic viscosity at 68 °F:Non-applicable *Concentration:Non-applicable *pH:10.5 - 11.5 at 100 %Vapour density at 68 °F:Non-applicable *Solubility in water at 68 °F:Non-applicable *Solubility in water at 68 °F:Non-applicable *Solubility properties:Non-applicable *Decomposition temperature:Non-applicable *Metting point/freezing point:Non-applicable *Explosive properties:Non-applicable *Oxidising properties:Non-applicable *Flammability:Flammability:Flammability (solid, gas):Non -applicable *		Volatility:				
Vapour pressure at 122 °F:91.55 (12.21 kPa)Evaporation rate at 68 °F:Non-applicable *Product description:Density at 68 °F:1040.2 kg/m³Relative density at 68 °F:1.04Dynamic viscosity at 68 °F:Non-applicable *Kinematic viscosity at 68 °F:Non-applicable *Kinematic viscosity at 68 °F:Non-applicable *Concentration:Non-applicable *PH:10.5 - 11.5 at 100 %Vapour density at 68 °F:Non-applicable *Solubility in water at 68 °F:Non-applicable *Solubility in water at 68 °F:Non-applicable *Solubility properties:Non-applicable *Solubility properties:Non-applicable *Partition coefficient n-octanol/water 68 °F:Non-applicable *Solubility properties:Non-applicable *Solubility properties:Non-applicable *Percomposition temperature:Non-applicable *Non-applicable *Non-applicable *Partition coefficient n-octanol/water 68 °F:Non-applicable *Solubility properties:Non-applicable *Solubility properties:Non-applicable *Percomposition temperature:Non-applicable *Non-applicable *Non-applicable *Partition coefficient n-octanolNon-applicable *Percomposition temperature:Non-applicable *Percomposition temperature:Non-applicable *Percomposition temperature:Non-applicable *Percomposition temperature:Non-applicable *Percomposition temperat		Boiling point at atmospheric pressure:	219 ºF			
Evaporation rate at 68 °F:Non-applicable *Product description:1040.2 kg/m³Density at 68 °F:1.04Dynamic viscosity at 68 °F:Non-applicable *Kinematic viscosity at 68 °F:Non-applicable *Kinematic viscosity at 68 °F:Non-applicable *Kinematic viscosity at 104 °F:>20.5 cStConcentration:Non-applicable *PH:10.5 - 11.5 at 100 %Vapour density at 68 °F:Non-applicable *Partition coefficient n-octanol/water 68 °F:Non-applicable *Solubility in water at 68 °F:Non-applicable *Solubility in water at 68 °F:Non-applicable *Solubility properties:Non-applicable *Decomposition temperature:Non-applicable *Melting point/freezing point:Non-applicable *Kining properties:Non-applicable *Oxidising properties:Non-applicable *Plammability:Non-applicable *Flammability:Non-applicable *Flammability (solid, gas):Non Plammable (>199.4 °F)		Vapour pressure at 68 °F:	2316 P	а		
Product description:Density at 68 °F:1040.2 kg/m³Relative density at 68 °F:1.04Dynamic viscosity at 68 °F:Non-applicable *Kinematic viscosity at 68 °F:Non-applicable *Kinematic viscosity at 104 °F:>20.5 cStConcentration:Non-applicable *PH:10.5 - 11.5 at 100 %Vapour density at 68 °F:Non-applicable *PH:0.5 - 11.5 at 100 %Vapour density at 68 °F:Non-applicable *Solubility in water at 68 °F:Non-applicable *Solubility in water at 68 °F:Non-applicable *Decomposition temperature:Non-applicable *Decomposition temperature:Non-applicable *Melting point/freezing point:Non-applicable *Explosive properties:Non-applicable *Oxidising properties:Non-applicable *Flammability:Non-applicable *Flammability (solid, gas):Non Flammable (>199.4 °F)Flammability (solid, gas):Non-applicable *		Vapour pressure at 122 °F:	91.55	91.55 (12.21 kPa)		
Density at 68 °F:1040.2 kg/m³Relative density at 68 °F:1.04Dynamic viscosity at 68 °F:Non-applicable *Kinematic viscosity at 68 °F:Non-applicable *Kinematic viscosity at 104 °F:>20.5 cStConcentration:Non-applicable *pH:10.5 - 11.5 at 100 %Vapour density at 68 °F:Non-applicable *Partition coefficient n-octanol/water 68 °F:Non-applicable *Solubility in water at 68 °F:Non-applicable *Solubility properties:Non-applicable *Decomposition temperature:Non-applicable *Melting point/freezing point:Non-applicable *Explosive properties:Non-applicable *Oxidising properties:Non-applicable *Flammability:Non-applicable *Flammability (solid, gas):Non Flammable (>199.4 °F)Flammability (solid, gas):Non-applicable *		Evaporation rate at 68 °F:	Non-ap	plicable *		
Relative density at 68 °F:1.04Dynamic viscosity at 68 °F:Non-applicable *Kinematic viscosity at 68 °F:Non-applicable *Kinematic viscosity at 104 °F:>20.5 cStConcentration:Non-applicable *pH:10.5 - 11.5 at 100 %Vapour density at 68 °F:Non-applicable *Partition coefficient n-octanol/water 68 °F:Non-applicable *Solubility in water at 68 °F:Non-applicable *Solubility properties:Non-applicable *Decomposition temperature:Non-applicable *Melting point/freezing point:Non-applicable *Explosive properties:Non-applicable *Oxidising properties:Non-applicable *Flammability:Kon-applicable *Flammability (solid, gas):Non Flammable (>199.4 °F)Flammability (solid, gas):Non-applicable *		Product description:				
Dynamic viscosity at 68 °F:Non-applicable *Kinematic viscosity at 68 °F:Non-applicable *Kinematic viscosity at 104 °F:>20.5 cStConcentration:Non-applicable *pH:10.5 - 11.5 at 100 %Vapour density at 68 °F:Non-applicable *Partition coefficient n-octanol/water 68 °F:Non-applicable *Solubility in water at 68 °F:Non-applicable *Solubility properties:Non-applicable *Decomposition temperature:Non-applicable *Melting point/freezing point:Non-applicable *Explosive properties:Non-applicable *Oxidising properties:Non-applicable *Flash Point:Non-applicable *Flammability:Non Flammable (>199.4 °F)Flammability (solid, gas):Non-applicable *		Density at 68 °F:	1040.2	kg/m³		
Kinematic viscosity at 68 °F:Non-applicable *Kinematic viscosity at 104 °F:>20.5 cStConcentration:Non-applicable *pH:10.5 - 11.5 at 100 %Vapour density at 68 °F:Non-applicable *Partition coefficient n-octanol/water 68 °F:Non-applicable *Solubility in water at 68 °F:Non-applicable *Solubility properties:Non-applicable *Decomposition temperature:Non-applicable *Melting point/freezing point:Non-applicable *Explosive properties:Non-applicable *Oxidising properties:Non-applicable *Flammability:Flammability:Flash Point:Non Flammable (>199.4 °F)Flammability (solid, gas):Non-applicable *		Relative density at 68 °F:	1.04			
Kinematic viscosity at 104 °F:>20.5 cStConcentration:Non-applicable *pH:10.5 - 11.5 at 100 %Vapour density at 68 °F:Non-applicable *Partition coefficient n-octanol/water 68 °F:Non-applicable *Solubility in water at 68 °F:Non-applicable *Solubility properties:Non-applicable *Decomposition temperature:Non-applicable *Melting point/freezing point:Non-applicable *Explosive properties:Non-applicable *Oxidising properties:Non-applicable *Flash Point:Non Flammable (>199.4 °F)Flammability (solid, gas):Non-applicable *		Dynamic viscosity at 68 °F:	Non-ap	plicable *		
Concentration:Non-applicable *pH:10.5 - 11.5 at 100 %Vapour density at 68 °F:Non-applicable *Partition coefficient n-octanol/water 68 °F:Non-applicable *Solubility in water at 68 °F:Non-applicable *Solubility properties:Non-applicable *Decomposition temperature:Non-applicable *Melting point/freezing point:Non-applicable *Explosive properties:Non-applicable *Oxidising properties:Non-applicable *Flammability:Non-applicable *Flash Point:Non Flammable (>199.4 °F)Flammability (solid, gas):Non-applicable *		Kinematic viscosity at 68 °F:	Non-ap	plicable *		
pH:10.5 - 11.5 at 100 %Vapour density at 68 °F:Non-applicable *Partition coefficient n-octanol/water 68 °F:Non-applicable *Solubility in water at 68 °F:Non-applicable *Solubility properties:Non-applicable *Decomposition temperature:Non-applicable *Melting point/freezing point:Non-applicable *Explosive properties:Non-applicable *Oxidising properties:Non-applicable *Flammability:Non-applicable *Flash Point:Non Flammable (>199.4 °F)Flammability (solid, gas):Non-applicable *		Kinematic viscosity at 104 °F:	>20.5 c	St		
Vapour density at 68 °F:Non-applicable *Partition coefficient n-octanol/water 68 °F:Non-applicable *Solubility in water at 68 °F:Non-applicable *Solubility properties:Non-applicable *Decomposition temperature:Non-applicable *Melting point/freezing point:Non-applicable *Explosive properties:Non-applicable *Oxidising properties:Non-applicable *Flammability:Non-applicable *Flash Point:Non-applicable *Flammability (solid, gas):Non Flammable (>199.4 °F)Flammability (solid, gas):Non-applicable *		Concentration:	Non-ap	plicable *		
Partition coefficient n-octanol/water 68 °F:Non-applicable *Solubility in water at 68 °F:Non-applicable *Solubility properties:Non-applicable *Decomposition temperature:Non-applicable *Melting point/freezing point:Non-applicable *Explosive properties:Non-applicable *Oxidising properties:Non-applicable *Flammability:Non-applicable *Flash Point:Non-applicable *Flammability (solid, gas):Non-applicable *		pH:	10.5 - 1	11.5 at 100 %		
Solubility in water at 68 °F:Non-applicable *Solubility properties:Non-applicable *Decomposition temperature:Non-applicable *Melting point/freezing point:Non-applicable *Explosive properties:Non-applicable *Oxidising properties:Non-applicable *Flammability:Flammability:Flash Point:Non Flammable (>199.4 °F)Flammability (solid, gas):Non-applicable *		Vapour density at 68 °F:	Non-ap	plicable *		
Solubility properties:Non-applicable *Decomposition temperature:Non-applicable *Melting point/freezing point:Non-applicable *Explosive properties:Non-applicable *Oxidising properties:Non-applicable *Flammability:Flammabile (>199.4 °F)Flammability (solid, gas):Non-applicable *		Partition coefficient n-octanol/water 68 °F:	Non-ap	plicable *		
Decomposition temperature:Non-applicable *Melting point/freezing point:Non-applicable *Explosive properties:Non-applicable *Oxidising properties:Non-applicable *Flammability:Flammabile (>199.4 °F)Flammability (solid, gas):Non-applicable *		Solubility in water at 68 °F:	Non-ap	plicable *		
Melting point/freezing point:Non-applicable *Explosive properties:Non-applicable *Oxidising properties:Non-applicable *Flammability:Flammability:Flash Point:Non Flammable (>199.4 °F)Flammability (solid, gas):Non-applicable *		Solubility properties:	Non-ap	plicable *		
Explosive properties:Non-applicable *Oxidising properties:Non-applicable *Flammability:Non Flammable (>199.4 °F)Flammability (solid, gas):Non-applicable *		Decomposition temperature:	Non-ap	plicable *		
Oxidising properties:Non-applicable *Flammability:Non Flammable (>199.4 °F)Flammability (solid, gas):Non-applicable *		Melting point/freezing point:	Non-ap	plicable *		
Flammability:Flash Point:Non Flammable (>199.4 °F)Flammability (solid, gas):Non-applicable *		Explosive properties:	Non-ap	plicable *		
Flash Point:Non Flammable (>199.4 °F)Flammability (solid, gas):Non-applicable *		Oxidising properties:	Non-ap	plicable *		
Flammability (solid, gas): Non-applicable *		Flammability:				
		Flash Point:	Non Fl	ammable (>199.4 °F)		
Autoignition temperature: 460 °F		Flammability (solid, gas):	Non-ap	plicable *		
		Autoignition temperature:	460 °F			
		Upper flammability limit:	Non-ar	plicable *		

*Not relevant due to the nature of the product, not providing information property of its hazards.



SEC	TION 9: PHYSICAL AND CHEMICA	L PROPERTIES (continued)	
	Explosive:		
	Lower explosive limit:	Non-applicable *	
	Upper explosive limit:	Non-applicable *	
9.2	Other information:		
	Surface tension at 68 °F:	Non-applicable *	
	Refraction index:	Non-applicable *	
	*Not relevant due to the nature of the product, no	providing information property of its hazards.	

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air Increase in temperature		Increase in temperature Sunlight	
Not applicable	Not applicable	Precaution	Precaution	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Not applicable	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. With possibility of effects that are hazardous to the health, it is recommended not to breathe the vapours for long periods of time.

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.

- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

- B- Inhalation (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces serious eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Exposure to this product can cause cancer. For more specific information on the possible health effects see section 2.
 - IARC: 2-butoxyethanol (3); Amides, coco, N,N-bis(hydroxyethyl) (2B); Diethanolamine (2B); 2,2',2''-nitrilotriethanol (3)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
 - Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, however, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	A	Acute toxicity	
Sodium Alkylsulfonates	LD50 oral	2290 mg/kg	Rat
CAS: Proprietary	LD50 dermal	6300 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	
2-butoxyethanol	LD50 oral	1414 mg/kg	Rat
CAS: 111-76-2	LD50 dermal	1060 mg/kg	Rabbit
	LC50 inhalation	11 mg/L (4 h)	Rat
Amides, coco, N,N-bis(hydroxyethyl)	LD50 oral	12200 mg/kg	Rat
CAS: 68603-42-9	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
Diethanolamine	LD50 oral	710 mg/kg	Rat
CAS: 111-42-2	LD50 dermal	12200 mg/kg	Rabbit
	LC50 inhalation	Non-applicable	

Acute Toxicity Estimate (ATE mix):

ATE mix		Ingredient(s) of unknown toxicity	
Oral	19808.45 mg/kg (Calculation method)	17.13 %	
Dermal	15372.65 mg/kg (Calculation method)	20.19 %	
Inhalation	118.9 mg/L (4 h) (Calculation method)	40.31 %	

SECTION 12: ECOLOGICAL INFORMATION



SECTION 12: ECOLOGICAL INFORMATION (continued)

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Ecotoxicity (aquatic and terrestrial, where available):

Identification	Acute toxicity		Species	Genus
Sodium Alkylsulfonates	LC50 4.2 mg/L (96 h)		Brachydanio rerio	Fish
CAS: Proprietary	EC50	4.53 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	5.2 mg/L (72 h)	Skeletonema costatum	Algae
2-butoxyethanol	LC50	1490 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 111-76-2	EC50	1815 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	911 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
Amides, coco, N,N-bis(hydroxyethyl)	LC50	3.6 mg/L (96 h)	Brachydanio rerio	Fish
CAS: 68603-42-9	EC50	4.2 mg/L (34 h)	Daphnia magna	Crustacean
	EC50	2.2 mg/L (96 h)	Scenedesmus subspicatus	Algae
Diethanolamine	LC50	800 mg/L (24 h)	Carassius auratus	Fish
CAS: 111-42-2	EC50	180 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	75 mg/L (72 h)	Scenedesmus subspicatus	Algae

12.2 Persistence and degradability:

Identification	De	egradability	Biodegradability	
Sodium Alkylsulfonates	BOD5	Non-applicable	Concentration	20 mg/L
CAS: Proprietary	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	96 %
2-butoxyethanol	BOD5	0.71 g O2/g	Concentration	100 mg/L
CAS: 111-76-2	COD	2.2 g O2/g	Period	14 days
	BOD5/COD	0.32	% Biodegradable	96 %
Diethanolamine	BOD5	0.03 g O2/g	Concentration	100 mg/L
CAS: 111-42-2	COD	1.52 g O2/g	Period	21 days
	BOD5/COD	0.02	% Biodegradable	54 %

12.3 Bioaccumulative potential:

Identification		Bioaccumulation potential	
Sodium Alkylsulfonates		BCF	71
CAS: Proprietary		Pow Log	-1.3
		Potential	Moderate
2-butoxyethanol		BCF	3
CAS: 111-76-2		Pow Log	0.83
		Potential	Low
Diethanolamine		BCF	1
CAS: 111-42-2		Pow Log	-1.43
		Potential	Low

12.4 Mobility in soil:

Identification	Absorp	Absorption/desorption		Volatility	
Sodium Alkylsulfonates	Кос	1.6	Henry	6.7E-2 Pa⋅m³/mol	
CAS: Proprietary	Conclusion	Very High	Dry soil	Yes	
	Surface tension	Non-applicable	Moist soil	Yes	
2-butoxyethanol	Кос	8	Henry	1.621E-1 Pa·m³/mol	
CAS: 111-76-2	Conclusion	Very High	Dry soil	No	
	Surface tension	2.729E-2 N/m (77 °F)	Moist soil	Yes	
Diethanolamine	Кос	Non-applicable	Henry	Non-applicable	
CAS: 111-42-2	Conclusion	Non-applicable	Dry soil	Non-applicable	
	Surface tension	3.4E-2 N/m (299.21 °F)	Moist soil	Non-applicable	

12.5 Results of PBT and vPvB assessment:

Non-applicable

12.6 Other adverse effects:



SECTION 12: ECOLOGICAL INFORMATION (continued)

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Disposal methods:

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations. In case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See epigraph 6.2.

Regulations related to waste management:

Legislation related to waste management:

40 CFR Part 261- IDENTIFICATION AND LISTING OF HAZARDOUS WASTE

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to 49 CFR on the Transport of Dangerous Goods:

With regard to 49 CFR on the Transport of Dangerous Goods:					
14.1	UN number:	Non-applicable			
14.2	UN proper shipping name:	Non-applicable			
14.3	Transport hazard class(es):	Non-applicable			
	Labels:	Non-applicable			
14.4	Packing group, if applicable:	Non-applicable			
14.5	Environmental hazard:	No			
14.6	Special precautions which a user transport or conveyance either w	needs to be aware of, or needs to comply with, in connection with ith ithin or outside their premises			
	Physico-Chemical properties:	see section 9			
14.7	Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):	Non-applicable			
Transpor	t of dangerous goods by sea:				
With rega	ard to IMDG 38-16:				
14.1	UN number:	Non-applicable			
14.2	UN proper shipping name:	Non-applicable			
14.3	Transport hazard class(es):	Non-applicable			
	Labels:	Non-applicable			
14.4	Packing group, if applicable:	Non-applicable			
14.5	Environmental hazard:	No			
14.6	14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises				
	Physico-Chemical properties:	see section 9			
14.7	Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):	Non-applicable			
Transport of dangerous goods by air:					
With regard to IATA/ICAO 2019:					



SECTION 14: TRANSPORT INFORMATION (continued)

14.1	UN number:	Non-applicable	
14.2	UN proper shipping name:	Non-applicable	
14.3	Transport hazard class(es):	Non-applicable	
	Labels:	Non-applicable	
14.4	Packing group, if applicable:	Non-applicable	
14.5	Environmental hazard:	No	
14.6	.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises		
	Physico-Chemical properties:	see section 9	
14.7	Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):	Non-applicable	

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations specific for the product in question:

SARA Title III - Toxic Chemical Release Inventory Reporting (Section 313): 2-butoxyethanol ; Diethanolamine California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986): Diethanolamine The Toxic Substances Control Act (TSCA) : Sodium Alkylsulfonates ; Anionic Surfactants ; 2-butoxyethanol ; Amides, coco, N,Nbis(hydroxyethyl) ; Diethanolamine

Massachusetts RTK - Substance List: Diethanolamine

New Jersey Worker and Community Right-to-Know Act: 2-butoxyethanol ; Diethanolamine

New York RTK - Substance list: 2-butoxyethanol ; Diethanolamine

Pennsylvania Worker and Community Right-to-Know Law: 2-butoxyethanol ; Diethanolamine

CANADA-Domestic Substances List (DSL): Sodium Alkylsulfonates ; Anionic Surfactants ; 2-butoxyethanol ; Amides, coco, N,N-bis(hydroxyethyl) ; Diethanolamine

CANADA-Non-Domestic Substances List (NDSL): Non-applicable

NTP (National Toxicology Program): Non-applicable

Minnesota - Hazardous substances ERTK: 2-butoxyethanol ; Diethanolamine

Rhode Island - Hazardous substances RTK: 2-butoxyethanol ; Diethanolamine

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096): Non-applicable

Hazardous substances release notification under CERCLA sections 102-103 (40 CFR Part 302): Diethanolamine (100 pounds)

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

Other legislation:

The Toxic Substances Control Act (TSCA) Occupational Safety and Health Standards (1910 Subpart Z - Toxic and Hazardous Substances)

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets

Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation

H318: Causes serious eye damage

H351: Suspected of causing cancer

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

29 CFR 1910.1200:



SECTION 16: OTHER INFORMATION (continued) Acute Tox. 4: H302 - Harmful if swallowed Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled Carc. 2: H351 - Suspected of causing cancer Eye Dam. 1: H318 - Causes serious eye damage Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Lig. 4: H227 - Combustible liquid Skin Irrit. 2: H315 - Causes skin irritation STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure Advice related to training: Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product. Principal bibliographical sources: Occupational Safety & Health Administration (OSHA). Abbreviations and acronyms: IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5-day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 CL50: Lethal Concentration 50 EC50: Effective concentration 50 Log-POW: Octanol-water partition coefficient Koc: Partition coefficient of organic carbon

Manufacturer Disclaimer: The information contained in this safety date sheet ("SDS") is based on sources, technical knowledge and current legislation. Furthermore, is based on data believed to be accurate; thus, the company does not assume any liability for its accuracy. The information provided herein cannot be considered a guarantee of the properties of this product and the same is simply a description of the security requirements. The use, occupational methodology and/or conditions for users of this product are not within our awareness or control. It is ultimately the responsibility of the user(s) to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information of this SDS only refers to this product, which should not be used for purposes other than those specified. Finally, the manner in which this product is used and whether there is any infringement of patents is the sole responsibility of the user(s).